Electrical Special Purpose Cable Assembly - Page 1 of 1



V 448-9566

View Online at https://aerobasegroup.com/nsn/6150-01-44
Cross Sectional Shape:
Round
Overall Length:
27.000 inches
Termination Type:
Connector both ends all conductors
Conductor Quantity:
20
Strand Quantity Per Conductor:
19 all conductors
Conductor Form:
Stranded all conductors
Product Name:
Cable, camera test, w32
Round Conductor Size:
26 awg all conductors
Strand Awg Size Per Conductor:
38 all conductors
Terminal Manufacturer Identifying Reference Number:
M83723/78w1624n 2nd end all conductors
Special Features:
C/o cable p/p m27500-26ml1t08: wire p/ps m81044/12-24.

C/o cable p/n m27500-26ml1t08; wire p/ns m81044/12-24-92, -90, -9; cable, rf p/n m17/45-rg108; nha p/n 337573; u/o p/ns 3028a-1, 1190a-10; cable assembly p/n 337632-2 same as -1 except connector p1 swap pins 20, 21 producing connectivity - p1-14 to p1-21, p1-13 and p2-21 to p1-20; change pin isgnal labels to p1-20 horizontal defl lo out, p1-21 horizontal defl hi out; -1 harness is not used w/an-aaq-15, an-aaq-17, an-aaq-8 or it will cause inverse composite video; all future procurements shall be -2 configuration Material:

Tin 4th position coating all conductors

Material Specification:

Astm b33 assn standard single material response core conductor all conductors

Surface Treatment:

Tin core conductor all conductors

Surface Treatment Specification:

Astmb33-63 assn standard single treatment response core conductor all conductors

Style Designator:

Internal connectors

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A077a0