## NSN 6150-01-467-2016

Electrical Special Purpose Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6150-01-467-2016

| View Online at https://aerobasegroup.com/nsn/6150-01-467-2016  |
|--|
| Cross Sectional Shape:   |
| Round  |
| Overall Length:  |
| 80.000 inches  |
| End Application:   |
| B-1b acft; next assembly p/n l5501526  |
| Termination Type:  |
| Connector receptacle 1st end all conductors  |
| Conductor Quantity:  |
| 68   |
| Strand Quantity Per Conductor:   |
| 19 all conductors  |
| Conductor Form:  |
| Stranded all conductors  |
| Product Name:  |
| Cable assembly-low voltage Ih, tds   |
| Round Conductor Size:  |
| 20 awg all conductors  |
| Strand Awg Size Per Conductor:   |
| 32 all conductors  |
| Terminal Manufacturer Identifying Reference Number:  |
| Le482-0077-2306 2nd end all conductors   |
| Terminal Commercial And Government Entity Code:  |
| 43999 2nd end all conductors   |
| Special Features:  |
| Retrofit eo I578988 incorporated; wire specs: m22759/41-20-9, m27500-20sm2u00, m27500-20sm3n23; model b-1r harness 6073a-a |
| Material:  |
| Plastic cross-linked modified ethylene tetrafluoroethylene 4th position jacket cable                                       |
| Material Specification:  |
| Astm b355 assn standard single material response core conductor all conductors   |
| Nuclear Hardness Critical Feature:   |
| Hardened   |
| Surface Treatment:   |
| Nickel core conductor all conductors   |
| Surface Treatment Specification:   |
| Astm b355 assn standard single treatment response core conductor all conductors  |
| Style Designator:  |
| Internal connectors  |
| Fsc Application Data:  |
| Aircraft accessory equipment   |
| Shelf Life:  |

N/a

## NSN 6150-01-467-2016

Electrical Special Purpose Cable Assembly - Page 2 of 2



|   |     | • - |    |     |    |    |    |    |
|---|-----|-----|----|-----|----|----|----|----|
|   | In  |     | Of | RЛ  | മാ | CI | ır | Δ. |
| L | ,,, |     |    | IVI | ca |    |    |    |

--

Demilitarization:

No

Fiig:

A077a0