## NSN 6150-01-472-1560

Electrical Special Purpose Cable Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6150-01-472-1560

Cross Sectional Shape:
Round
Overall Length:
8.000 feet
End Application:
5450-01-359-3350
Termination Type:
Connector internal straight both ends single conductor
Conductor Quantity:
1
Strand Quantity Per Conductor:
19 single conductor
Conductor Form:
Stranded single conductor
Round Conductor Size:
20 awg single conductor
Strand Awg Size Per Conductor:
Strain Awy Size Fer Conductor.
33 single conductor
-
33 single conductor
33 single conductor  Material:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli
33 single conductor  Material:  Plastic polyethylene 1st position primary insulation single conductor  Surface Treatment:  Tin 2nd position shield braid, metallic single conductor  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  Yes - demil/mli  Fiig: