## NSN 6150-01-530-1523

Electrical Special Purpose Cable Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6150-01-530-1523

| Cross Sectional Shape:   |
|--|
| Round  |
| Overall Length:  |
| 40.000 inches  |
| Outside Diameter:  |
| 0.515 inches all conductors  |
| Termination Type:  |
| Connector plug 2nd end all conductors  |
| Conductor Quantity:  |
| 3  |
| Strand Quantity Per Conductor:   |
| 65 all conductors  |
| Conductor Form:  |
| Stranded all conductors  |
| Round Conductor Size:  |
| 12 awg all conductors  |
| Strand Awg Size Per Conductor:   |
| 30 all conductors  |
| Conductor Cross-sectional Shape:   |
| Tubular braid all conductors   |
| Terminal Manufacturer Identifying Reference Number:  |
| Ms3475w14-4sw 1st end all conductors   |
| Terminal Commercial And Government Entity Code:  |
| 96906 both ends all conductors   |
| Special Features:  |
| Item must retain end to end continuity of less than 3 ohms, with dielectric strngth of 500vdc for not less than 30 seconds. Insulation |
| resistance of not less than 100 megohms whn tested iaw mil-std-202, method 302, test condition b. Mark cable as indicated.             |
| Color:   |
| White core conductor second conductor  |
| Material:  |
| Copper core conductor all conductors   |
| Precious Material And Location:  |
| In both connectors, the contact surfaces are gold. Gold  |
| Precious Material:   |
| Gold   |
| Surface Treatment:   |
| Tin core conductor all conductors  |
| Style Designator:  |
| Internal angle and internal straight connector   |
| Shelf Life:  |
| N/a  |

--

**Unit Of Measure:** 

## NSN 6150-01-530-1523

Electrical Special Purpose Cable Assembly - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A077a0