NSN 6150-01-575-9843

Electrical Lead - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6150-01-575-9843

| view Crimine at https://doi.oba.obg/coap.com/mon/crico or ore confe |
|--|
| Cross Sectional Shape: |
| Twist |
| Cross Section Outside Diameter: |
| 0.083 inches |
| End Application: |
| Aircraft applications |
| Termination Type: |
| Lug terminal w/mounting hole both ends single conductor |
| Leadlength: |
| Between 10.000 inches and 10.250 inches |
| Strand Quantity Per Conductor: |
| 7 single conductor |
| Conductor Form: |
| Stranded single conductor |
| Product Name: |
| Bonding jumper assembly |
| Round Conductor Size: |
| 12 awg single conductor |
| Strand Awg Size Per Conductor: |
| 37 single conductor |
| Terminal Lug Aperture Size: |
| 0.112 inches both ends single conductor |
| Terminal Manufacturer Identifying Reference Number: |
| Sae-as25036-111 both ends single conductor |
| Terminal Commercial And Government Entity Code: |
| 80205 both ends single conductor |
| Lead Pull Strength: |
| 110.0 pounds |
| Special Features: |
| Not fuel compatible; attached terminals are crimped; not lightening tested; insulated |
| Special Markings: |
| None-no color band |
| Material: |
| Copper core conductor single conductor |
| Material Specification: |
| A-a-59551, type r, temper 1 assn standard single material response core conductor single conductor |
| Surface Treatment: |
| Tin core conductor single conductor |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 6150-01-575-9843

Electrical Lead - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A077a0