NSN 6210-00-019-0130

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-019-0130

Overall Length:
2.609 inches
Overall Diameter:
Between 1.355 inches and 1.395 inches
Lamp Base Type Accommodated:
Double contact bayonet candelabra
Lamp Bulb Size Designator:
S-6
Lens Quantity:
1
Lens Color:
Green single light 1st position horizontal
Panel Accommodation Hole Diameter:
1.000 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.344 inches
Lamp Type Accommodated And Quantity:
1 neon
Heon
Lens Type:
Lens Type:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body Style Designator:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body Style Designator: Round frame, round lens type

2 solder lug

NSN 6210-00-019-0130

Indicator Light - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0