## NSN 6210-00-042-9712

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-042-9712

Overall Length:
1.906 inches
Overall Diameter:
0.875 inches
Lamp Base Type Accommodated:
Miniature bayonet
Lamp Bulb Size Designator:
G-3 1/2
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.750 inches
Lens Mounting Method:
Push in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.250 inches
Lamp Type Accommodated And Quantity:
1 incandescent
1 incandescent
1 incandescent  Lens Type:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Steel body
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Steel body  Surface Treatment:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Steel body  Surface Treatment:  Cadmium body
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Steel body  Surface Treatment:  Cadmium body  Style Designator:
1 incandescent  Lens Type:  Convex, small bubble single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Steel body  Surface Treatment:  Cadmium body  Style Designator:  Round frame, round lens type

1 wire lead

## NSN 6210-00-042-9712

Indicator Light - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A065a0