

View Online at <https://aerobasegroup.com/nsn/6210-00-080-1058>

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

2.666 inches

Overall Diameter:

Between 0.938 inches and 0.968 inches

Lamp Base Type Accommodated:

Miniature bayonet

Lamp Bulb Size Designator:

T-3 1/4

Lens Quantity:

1

Lens Color:

Colorless single light 1st position horizontal

Panel Accommodation Hole Diameter:

Between 0.688 inches and 0.694 inches

End Application:

An/sqq-89 surface ship asw combat system; spruance class dd (963); kidd class ddg; ticonderoga class cg (47)

Lens Mounting Method:

Screw in

Mounting Method:

Panel

Panel Thickness For Which Designed:

0.344 inches

Features Provided:

Blackout degree, partial and dimming device

Lamp Type Accommodated And Quantity:

1 incandescent

Lens Type:

Convex, knurled, threaded shank single light 1st position horizontal

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Light Color:

Colorless single light 1st position horizontal full display division a

Lens Back Surface Condition:

Frosted single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Special Features:

Dim arrow symbol cw and bright arrow symbol ccw

Material:

Copper alloy body

Surface Treatment:

Nickel body

Style Designator:

Round frame, round lens type

Furnished Items And Quantity:

1 gasket and 1 hexagon nut and 1 lock washer

Terminal Type And Quantity:

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A065a0

Mil-std (military Standard):

Mil-I-3661 spec.