NSN 6210-00-115-9150

Lighting Fixture - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-115-9150

| View Online at https://aerobasegroup.com/nsn/6210-00-115-9150 |
|---|
| Hazardous Locations/environmental Protection: |
| Dripproof and shock resistant and vibration resistant |
| Overall Length: |
| 25.250 inches |
| Overall Height: |
| 4.500 inches |
| Overall Width: |
| 23.750 inches |
| Lamp Base Type Accommodated: |
| Medium bipin |
| Wiring Provision Method: |
| Cable |
| Illumination Directing Device Type: |
| Window |
| Wiring Provision Length: |
| 120.0 inches single provision |
| Voltage Rating In Volts: |
| 120.0 ac |
| Mounting Method: |
| Flush |
| Lamp Type Accommodated And Quantity: |
| 6 fluorescent |
| Material: |
| Plastic illumination directing device |
| Material Specification: |
| Mil-p-24191, type clear 2 military specification single material response illumination directing device |
| Unpackaged Unit Weight: |
| 27.000 pounds |
| Surface Treatment: |
| Any acceptable body |
| Shape: |
| Rectangular |
| Furnished Items And Quantity: |
| 6 lamp and 1 type i labels and 1 type iv labels |
| Terminal Type And Quantity: |
| 1 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 6210-00-115-9150

Lighting Fixture - Page 2 of 2

Fiig: A06300 Mil-std (military Standard):

Mil-p-24191 spec.

