## NSN 6210-00-145-1217

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-145-1217

| hazardous Locations/environmental Protection:                      |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Radio frequency interference                                       |  |  |  |  |  |  |
| Overall Length:  |  |  |  |  |  |  |
| 1.750 inches   |  |  |  |  |  |  |
| Overall Diameter:  |  |  |  |  |  |  |
| 0.547 inches   |  |  |  |  |  |  |
| Lens Quantity:   |  |  |  |  |  |  |
| 1  |  |  |  |  |  |  |
| Lens Color:  |  |  |  |  |  |  |
| Amber single light 1st position horizontal                         |  |  |  |  |  |  |
| Panel Accommodation Hole Diameter:                                 |  |  |  |  |  |  |
| 0.375 inches   |  |  |  |  |  |  |
| Lens Mounting Method:  |  |  |  |  |  |  |
| Screw on   |  |  |  |  |  |  |
| Mounting Method:   |  |  |  |  |  |  |
| Panel  |  |  |  |  |  |  |
| Panel Thickness For Which Designed:                                |  |  |  |  |  |  |
| 0.219 inches   |  |  |  |  |  |  |
| Lamp Type Accommodated And Quantity:                               |  |  |  |  |  |  |
| 1 neon lamp cartridge  |  |  |  |  |  |  |
| Lens Type:   |  |  |  |  |  |  |
| Cylindrical, knurled single light 1st position horizontal          |  |  |  |  |  |  |
| Lens Light Transmission Characteristic:                            |  |  |  |  |  |  |
| Transparent single light 1st position horizontal                   |  |  |  |  |  |  |
| Transmitted Light Color:   |  |  |  |  |  |  |
| Amber single light 1st position horizontal full display division a |  |  |  |  |  |  |
| Lens Back Surface Condition:                                       |  |  |  |  |  |  |
| Smooth single light 1st position horizontal                        |  |  |  |  |  |  |
| Lens Face Surface Condition:                                       |  |  |  |  |  |  |
| Smooth single light 1st position horizontal                        |  |  |  |  |  |  |
| Material:  |  |  |  |  |  |  |
| Aluminum body  |  |  |  |  |  |  |
| Surface Treatment:   |  |  |  |  |  |  |
| Anodize body   |  |  |  |  |  |  |
| Style Designator:  |  |  |  |  |  |  |
| Round frame, round lens type                                       |  |  |  |  |  |  |
| Furnished Items And Quantity:                                      |  |  |  |  |  |  |
| 1 hexagon nut and 1 knurled flange ring and 1 lock washer          |  |  |  |  |  |  |
| Terminal Type And Quantity:  |  |  |  |  |  |  |
| 2 solder lug   |  |  |  |  |  |  |
| Shelf Life:  |  |  |  |  |  |  |
| N/a  |  |  |  |  |  |  |

## NSN 6210-00-145-1217

Indicator Light - Page 2 of 2



|    | • • |             |     |     |      |
|----|-----|-------------|-----|-----|------|
| In | 18  | <i>(</i> )+ | МЛО | 201 | ure: |
|    |     |             |     |     |      |

--

Demilitarization:

No

Fiig:

A065a0