NSN 6210-00-208-0439

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-208-0439

view Offilitie at https://aerobasegroup.com/histi/0210-00-200-0439
Overall Length:
3.172 inches
Overall Diameter:
1.375 inches
Lamp Base Type Accommodated:
Double contact bayonet candelabra
Lamp Bulb Size Designator:
S-6
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Panel Accommodation Hole Diameter:
1.000 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.625 inches
Lamp Type Accommodated And Quantity:
p : , , p :
1 incandescent
1 incandescent
1 incandescent Lens Type:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body Style Designator:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Grooved single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body Style Designator: Round frame, round lens type

2 screw

NSN 6210-00-208-0439

Indicator Light - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0