NSN 6210-00-225-9745

Indicator Light - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6210-00-225-9745 |
|--|
| Hazardous Locations/environmental Protection: |
| Dusttight and oiltight and watertight |
| Overall Length: |
| 1.234 inches |
| Overall Diameter: |
| 0.641 inches |
| Lamp Base Type Accommodated: |
| Midget flanged |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| White, translucent single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| 0.469 inches |
| End Application: |
| Forrestal class cv; cvn 68 class reactor fill auxiliary system; spruance class dd (963); submarine antenna; oliver perry class ffg; kidd class |
| ddg; nimitz class cvn; los angeles class ssn (688); deep submergence systems programs (dssp); ticonderoga class cg (47) |
| Lens Mounting Method: |
| Screw in |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.188 inches |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Lens Type: |
| Stovepipe, external thread single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Transmitted Light Color: |
| White, translucent single light 1st position horizontal full display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Special Features: |
| Black body |
| Material: |
| Aluminum body |

Anodize body

Surface Treatment:

NSN 6210-00-225-9745

Indicator Light - Page 2 of 2



| Style | Designa | ator |
|-------|-------------|------|
| D | al fue as a | |

Round frame, round lens type

Furnished Items And Quantity:

1 hexagon nut and 1 lock washer

Terminal Type And Quantity:

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0