Indicator Light - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6210-00-231-4113

| Hazardous Locations/environmental Protection: |
|--|
| Watertight |
| Overall Length: |
| 2.437 inches |
| Overall Diameter: |
| 0.828 inches |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Red single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| 0.688 inches |
| Lens Mounting Method: |
| Screw in |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.344 inches |
| Features Provided: |
| Dimming device and blackout degree, partial |
| Lens Type: |
| Convex, knurled, threaded shank single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Lens Back Surface Condition: |
| Frosted single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Special Features: |
| Dimming device mechanical shutter |
| Style Designator: |
| Round frame, round lens type |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Fiig: A065a0 |
| 7000a0 |
| |