NSN 6210-00-244-1966

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-244-1966

| Hazardous Locations/environmental Protection: |
|---|
| Oiltight and watertight |
| Overall Length: |
| 2.109 inches |
| Overall Diameter: |
| 0.828 inches |
| Lamp Base Type Accommodated: |
| Miniature bayonet |
| Lamp Bulb Size Designator: |
| T-3 1/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Red single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| 0.688 inches |
| Lamp Industry Number: |
| B1a |
| Lens Mounting Method: |
| Screw on |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.312 inches |
| Lamp Type Accommodated And Quantity: |
| 1 neon |
| Lens Type: |
| Dome, knurled, internal thread single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Transparent single light 1st position horizontal |
| Transmitted Light Color: |
| Red single light 1st position horizontal full display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Material: |
| Copper alloy body |
| Surface Treatment: |
| |
| Nickel body |

Round frame, round lens type

NSN 6210-00-244-1966

Indicator Light - Page 2 of 2



| Furni | ished | Items | And | Quantity | / : |
|-------|-------|--------------|-----|----------|------------|
| | | | | | |

1 gasket and 1 hexagon nut and 1 lock washer and 2 o-ring

Terminal Type And Quantity:

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A065a0