NSN 6210-00-299-7785

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-299-7785

Overall Length: 1.265 inches Lamp Base Type Accommodated: Midget flanged Lamp Bulb Size Designator: T1-3/4 Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition:
Lamp Base Type Accommodated: Midget flanged Lamp Bulb Size Designator: T1-3/4 Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lamp Bulb Size Designator: T1-3/4 Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lamp Bulb Size Designator: T1-3/4 Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Quantity: 1 Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Color: Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Green single light 1st position horizontal Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Panel Accommodation Hole Diameter: 0.469 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Mounting Method: Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Translucent single light 1st position horizontal Lens Back Surface Condition: Frosted single light 1st position horizontal
Lens Back Surface Condition: Frosted single light 1st position horizontal
Frosted single light 1st position horizontal
Lens Face Surface Condition:
Lens race durace donation.
Frosted single light 1st position horizontal
Special Features:
Insulated mounting
Material:
Copper alloy body
Surface Treatment:
Nickel body
Style Designator:
Round frame, round lens type
Round frame, round lens type Terminal Type And Quantity:
Terminal Type And Quantity:
Terminal Type And Quantity: 1 tab, solder lug

--

NSN 6210-00-299-7785

Indicator Light - Page 2 of 2



Demilitarization:

No

Fiig:

A065a0