

View Online at <https://aerobasegroup.com/nsn/6210-00-470-7602>

Thread Class:

2b

Thread Direction:

Right-hand

Thread Length:

Between 0.137 inches and 0.142 inches

Hazardous Locations/environmental Protection:

Heat resistant

Overall Length:

0.500 inches

Mounting Device Quantity:

1

Overall Diameter:

Between 0.501 inches and 0.531 inches

Effective Diameter:

Between 0.388 inches and 0.428 inches

End Application:

Bgun fire control system, mk 68; los angeles class ssn (688); virginia class cgn (41); ticonderoga class cg (47); an/spn-43b, 43c; teletype, model 28; deep submergence systems programs (dssp); fire pumps; sturgeon class ssn (637); integrated launch & recovery tv surveillance sys (ilarts); simulator an/mpq-t3; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j

Mounting Method:

Internal thread

Thread Series:

Unef

Features Provided:

Rotatable alignment capability

Light Transmission Design:

Translucent lens

Thread Quantity:

32 per inch

Holder Surface Treatment:

Anodize

Thread Diameter:

0.375 inches

Holder Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Color:

Red lens

Material:

Plastic polycarbonate lens

Material Specification:

Qq-a-225/3 federal specification single material response holder

Surface Condition:

Smooth back

Style Designator:

Cylindrical

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528d0

Mil-std (military Standard):

Mil-a-8625 spec.