

View Online at <https://aerobasegroup.com/nsn/6210-00-470-7602>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.137 inches and 0.142 inches

**Hazardous Locations/environmental Protection:**

Heat resistant

**Overall Length:**

0.500 inches

**Mounting Device Quantity:**

1

**Overall Diameter:**

Between 0.501 inches and 0.531 inches

**Effective Diameter:**

Between 0.388 inches and 0.428 inches

**End Application:**

Bgun fire control system, mk 68; los angeles class ssn (688); virginia class cgn (41); ticonderoga class cg (47); an/spn-43b, 43c; teletype, model 28; deep submergence systems programs (dssp); fire pumps; sturgeon class ssn (637); integrated launch & recovery tv surveillance sys (ilarts); simulator an/mpq-t3; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j

**Mounting Method:**

Internal thread

**Thread Series:**

Unef

**Features Provided:**

Rotatable alignment capability

**Light Transmission Design:**

Translucent lens

**Thread Quantity:**

32 per inch

**Holder Surface Treatment:**

Anodize

**Thread Diameter:**

0.375 inches

**Holder Surface Treatment Specification:**

Mil-a-8625 military specification single treatment response

**Color:**

Red lens

**Material:**

Plastic polycarbonate lens

**Material Specification:**

Qq-a-225/3 federal specification single material response holder

**Surface Condition:**

Smooth back

**Style Designator:**

Cylindrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528d0

**Mil-std (military Standard):**

Mil-a-8625 spec.