NSN 6210-00-488-1940

Panel Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-488-1940

Overall Length:
Between 0.449 inches and 0.496 inches
Overall Diameter:
0.375 inches
Lamp Base Type Accommodated:
Submidget flanged
Lamp Bulb Size Designator:
C-1
Lens Quantity:
1
Lens Color:
Red, aviation single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.312 inches
Mounting Method:
Panel
Panel Thickness For Which Designed:
Between 0.449 inches and 0.496 inches
Lamp Type Accommodated And Quantity:
1 incandescent
Lens Type:
*·
Flat, edge w/boot single light 1st position horizontal
Flat, edge w/boot single light 1st position horizontal
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Paint illumination directing device
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Paint illumination directing device Style Designator:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Paint illumination directing device Style Designator: Trap type
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Paint illumination directing device Style Designator: Trap type Terminal Type And Quantity:
Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Paint illumination directing device Style Designator: Trap type Terminal Type And Quantity: 2 solder stud

--

NSN 6210-00-488-1940

Panel Light - Page 2 of 2



Demilitarization:

No

Fiig:

A065a0