NSN 6210-00-490-5264

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-490-5264

Hazardous Locations/environmental Protection:
Radio frequency interference
Overall Length:
1.891 inches
Overall Diameter:
0.547 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.375 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.219 inches
Lamp Type Accommodated And Quantity:
Administration
1 incandescent
Lens Type:
Lens Type:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment:
Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Anodize body

1 hexagon nut and 1 lock washer

NSN 6210-00-490-5264

Indicator Light - Page 2 of 2



Terminal Type And Quantity	/ :
----------------------------	------------

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0