

View Online at <https://aerobasegroup.com/nsn/6210-00-538-1951>

Hazardous Locations/environmental Protection:

Radio frequency interference

Overall Length:

1.812 inches

Overall Height:

0.960 inches

Overall Width:

1.200 inches

Filter Color:

Blue single light 1st position horizontal full display division a and yellow single light 1st position horizontal full display division a

Lamp Base Type Accommodated:

Midget flanged

Lamp Bulb Size Designator:

T-1 3/4

Lens Quantity:

1

Lens Color:

Colorless single light 1st position horizontal

Filter Quantity:

4

Multilamp Circuit Type:

Four lamp common

Lamp Industry Number:

387

Lens Mounting Method:

Push in

Mounting Method:

Panel

Panel Thickness For Which Designed:

0.250 inches

Features Provided:

Removable light filter

Panel Accommodation Hole Width:

1.115 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, narrow single light 1st position horizontal

Panel Accommodation Hole Height:

0.875 inches

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Legend Color:

Black single light 1st position horizontal full display division a

Lens Legend:

Tim msl; on rail single light 1st position horizontal full display division a

Transmitted Light Color:

Blue single light 1st position horizontal full display division a and yellow single light 1st position horizontal full display division a

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Stainless steel body

Precious Material And Location:

Screen silver

Precious Material And Weight:

0.040 silver grains, troy

Precious Material:

Silver

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

5 solder stud

Reference Number Differentiating Characteristics:

As differentiated by extra long reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0

Mil-std (military Standard):

Mil-prf-22885 spec.