NSN 6210-00-539-8151

Indicator Light - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6210-00-539-8151 |
|------------------------------------------------------------------------------|
| Hazardous Locations/environmental Protection: |
| Dripproof |
| Overall Length: |
| 3.102 inches |
| Overall Diameter: |
| Between 1.344 inches and 1.406 inches |
| Lamp Base Type Accommodated: |
| Double contact bayonet candelabra |
| Lamp Bulb Size Designator: |
| S-6 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| White, aviation single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| Between 1.000 inches and 1.006 inches |
| Lens Mounting Method: |
| Screw on |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.188 inches |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Lens Type: |
| Dome, knurled, internal thread single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Transmitted Light Color: |
| White, aviation single light 1st position horizontal full display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Style Designator: |
| Round frame, round lens type |
| Furnished Items And Quantity: |
| 2 gasket and 1 hexagon nut and 1 lock washer and 1 flange |
| Terminal Type And Quantity: |
| 2 solder lug |
| Shelf Life: |

N/a

NSN 6210-00-539-8151

Indicator Light - Page 2 of 2



| ı | 1 | :. | ~ | 8.4 | | | |
|---|----|----|-----|-----|----|-----|------|
| ι | JN | ıτ | OI. | IVI | eа | เรเ | ıre: |

--

Demilitarization:

No

Fiig:

A065a0

Mil-std (military Standard):

Mil-I-3661 spec.