NSN 6210-00-579-1868

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-579-1868

Overall Length: 2.680 inches Overall Height: 0.812 inches Overall Width: 0.812 inches Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Overall Height: 0.812 inches Overall Width: 0.812 inches Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Overall Width: O.812 inches Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Overall Width: 0.812 inches Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
0.812 inches Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lamp Base Type Accommodated: Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Miniature bayonet Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
T-3 1/4 Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Quantity: 1 Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Color: Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Accommodation Hole Diameter: Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Between 0.625 inches and 0.630 inches Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Mounting Method: Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Push in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Thickness For Which Designed: 0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
0.375 inches Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Features Provided: Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Press to test Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
1 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Light Transmission Characteristic:
-
Translucent single light 1st position horizontal
Handidoon dingle light for position honzontal
Transmitted Legend Color:
Yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal full display division a
Lens Legend:
Failed; brg single light 1st position horizontal full display division a
Transmitted Light Color:
Black, opaque single light 1st position horizontal full display division a
Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Painted single light 1st position horizontal
Special Features:
Index locations b6

NSN 6210-00-579-1868

Indicator Light - Page 2 of 2



Material:
Aluminum alloy body
Surface Treatment:
Anodize body
Style Designator:
Round frame, rectangular lens type
Furnished Items And Quantity:
3 flat washer and 1 hexagon nut and 3 lock washer
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

A065a0