NSN 6210-00-669-6360

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-669-6360

Hazardous Locations/environmental Protection:
Radio frequency interference
Overall Length:
0.562 inches
Overall Diameter:
0.250 inches
Lens Quantity:
1
Lens Color:
Yellow single light 1st position horizontal
Panel Accommodation Hole Diameter:
Between 0.190 inches and 0.196 inches
Lamp Industry Number:
683
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.188 inches
Lamp Type Accommodated And Quantity:
Lamp Type Accommodated And Quantity: 1 incandescent
1 incandescent
1 incandescent Lens Type:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body Style Designator:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body Style Designator: Round frame, round lens type
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body Style Designator: Round frame, round lens type Furnished Items And Quantity:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Yellow single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body Style Designator: Round frame, round lens type Furnished Items And Quantity: 1 hexagon nut

N/a

NSN 6210-00-669-6360 Indicator Light - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A065a0