NSN 6210-00-724-8424

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-724-8424

Overall Length:
1.218 inches
Overall Diameter:
Between 0.550 inches and 0.553 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Red, identification single light 1st position horizontal
Panel Accommodation Hole Diameter:
Between 0.468 inches and 0.472 inches
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.188 inches
Lamp Type Accommodated And Quantity:
Lump Type Accommodated And Quantity.
1 incandescent
1 incandescent
1 incandescent Lens Type:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Anodize body
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Anodize body Style Designator:
1 incandescent Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red, identification single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Anodize body Style Designator: Round frame, round lens type

2 solder lug

NSN 6210-00-724-8424

Indicator Light - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0