## NSN 6210-00-779-3996

Indicator Light - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6210-00-779-399     |
|--|
| Hazardous Locations/environmental Protection:                    |
| Dusttight and oiltight and watertight                            |
| Overall Length:  |
| 1.234 inches   |
| Overall Diameter:  |
| 0.641 inches   |
| Lamp Base Type Accommodated:                                     |
| Midget flanged   |
| Lamp Bulb Size Designator:                                       |
| T-1 3/4  |
| Lens Quantity:   |
| 1  |
| Lens Color:  |
| Red single light 1st position horizontal                         |
| Panel Accommodation Hole Diameter:                               |
| 0.469 inches   |
| Lens Mounting Method:  |
| Screw in   |
| Mounting Method:   |
| Panel  |
| Panel Thickness For Which Designed:                              |
| 0.188 inches   |
| Lamp Type Accommodated And Quantity:                             |
| 1 incandescent   |
| Lens Type:   |
| Stovepipe, short shank single light 1st position horizontal      |
| Lens Light Transmission Characteristic:                          |
| Transparent single light 1st position horizontal                 |
| Transmitted Light Color:   |
| Red single light 1st position horizontal full display division a |
| Lens Back Surface Condition:                                     |
| Smooth single light 1st position horizontal                      |
| Lens Face Surface Condition:                                     |
| Smooth single light 1st position horizontal                      |
| Material:  |
| Aluminum body  |
| Surface Treatment:   |
| Anodize body   |
| Style Designator:  |
| Round frame, round lens type                                     |

**Furnished Items And Quantity:** 

1 hexagon nut and 1 lock washer

## NSN 6210-00-779-3996

Indicator Light - Page 2 of 2



2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0