NSN 6210-00-812-3488

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-812-3488

Hazardous Locations/environmental Protection:							
Watertight							
Overall Length:							
1.281 inches							
Overall Diameter:							
0.562 inches							
Lamp Base Type Accommodated:							
Midget flanged							
Lamp Bulb Size Designator:							
T-1 3/4							
Lens Quantity:							
1							
Lens Color:							
Amber single light 1st position horizontal							
Panel Accommodation Hole Diameter:							
0.469 inches							
Lens Mounting Method:							
Screw in							
Mounting Method:							
Panel							
Panel Thickness For Which Designed:							
0.250 inches							
Lamp Type Accommodated And Quantity:							
1 incandescent							
Lens Type:							
Lens Type: Stovepipe, short shank single light 1st position horizontal							
Stovepipe, short shank single light 1st position horizontal							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic:							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition:							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Nickel body							
Stovepipe, short shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:							

2 hexagon nut and 1 lock washer

NSN 6210-00-812-3488

Indicator Light - Page 2 of 2



	Ī	erm	inal	Type	And	Quantit	y:
--	---	-----	------	-------------	-----	---------	----

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0