NSN 6210-00-840-0503

Indicator Light - Page 1 of 2

Overall Length:



View Online at https://aerobasegroup.com/nsn/6210-00-840-0503

| 1.843 inches | | | | | | |
|--|--|--|--|--|--|--|
| Overall Diameter: | | | | | | |
| 0.718 inches | | | | | | |
| Lamp Base Type Accommodated: | | | | | | |
| Midget flanged | | | | | | |
| Lamp Bulb Size Designator: | | | | | | |
| T-1-3/4 | | | | | | |
| Lens Quantity: | | | | | | |
| 1 | | | | | | |
| Lens Color: | | | | | | |
| Red single light 1st position horizontal | | | | | | |
| Panel Accommodation Hole Diameter: | | | | | | |
| 0.500 inches | | | | | | |
| Lens Mounting Method: | | | | | | |
| Screw in | | | | | | |
| Mounting Method: | | | | | | |
| Panel | | | | | | |
| Panel Thickness For Which Designed: | | | | | | |
| 0.250 inches | | | | | | |
| Lamp Type Accommodated And Quantity: | | | | | | |
| 1 incandescent | | | | | | |
| Lens Type: | | | | | | |
| Convex, knurled single light 1st position horizontal | | | | | | |
| Lens Light Transmission Characteristic: | | | | | | |
| Translucent single light 1st position horizontal | | | | | | |
| Lens Back Surface Condition: | | | | | | |
| Smooth single light 1st position horizontal | | | | | | |
| Lens Face Surface Condition: | | | | | | |
| Smooth single light 1st position horizontal | | | | | | |
| Material: | | | | | | |
| Aluminum body | | | | | | |
| Surface Treatment: | | | | | | |
| Anodize body | | | | | | |
| Style Designator: | | | | | | |
| Round frame, round lens type | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 3 solder lug | | | | | | |
| Reference Number Differentiating Characteristics: | | | | | | |
| As modifid by reply to pac aewq | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 6210-00-840-0503 Indicator Light - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

Demilitarization:

No

Fiig:

A065a0