NSN 6210-00-851-9015

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-851-9015

View Online at https://aerobasegroup.com/nsn/6210-00-851-9015						
Hazardous Locations/environmental Protection:						
Dripproof						
Overall Length:						
3.235 inches						
Overall Diameter:						
Between 1.344 inches and 1.406 inches						
Lamp Base Type Accommodated:						
Double contact bayonet candelabra						
Lamp Bulb Size Designator:						
S-6						
Lens Quantity:						
1						
Lens Color:						
Green, aviation single light 1st position horizontal						
Panel Accommodation Hole Diameter:						
Between 1.000 inches and 1.006 inches						
Lens Mounting Method:						
Screw on						
Mounting Method:						
Panel						
Panel Thickness For Which Designed:						
0.188 inches						
Laws Town Assessment dated And Overtities						
Lamp Type Accommodated And Quantity:						
1 incandescent						
1 incandescent						
1 incandescent Lens Type:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Round frame, round lens type						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Round frame, round lens type Furnished Items And Quantity:						
1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Green, aviation single light 1st position horizontal full display division a Lens Back Surface Condition: Frosted single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Round frame, round lens type Furnished Items And Quantity: 2 gasket and 1 hexagon nut and 1 lock washer and 1 flange						

N/a

NSN 6210-00-851-9015

Indicator Light - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A065a0

Mil-std (military Standard):

Mil-I-3661 spec.