NSN 6210-00-881-8163

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-881-8163

Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
2.085 inches
Overall Diameter:
0.906 inches
Lamp Base Type Accommodated:
Miniature bayonet
Lamp Bulb Size Designator:
T-3 1/4
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
Between 0.688 inches and 0.694 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Lamp Type Accommodated And Quantity:
1 incandescent
Lens Type:
Convex, knurled, threaded shank single light 1st position horizontal
Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Light Transmission Characteristic:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity: 2 solder lug
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity: 2 solder lug Shelf Life:
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity: 2 solder lug Shelf Life: N/a
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity: 2 solder lug Shelf Life: N/a
Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Style Designator: Shell frame type Terminal Type And Quantity: 2 solder lug Shelf Life: N/a Unit Of Measure:

A065a0

NSN 6210-00-881-8163

Indicator Light - Page 2 of 2



Mil-std (military Standard):

Mil-I-3661 spec.