NSN 6210-00-892-6278

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-892-6278

| Hazardous Locations/environmental Protection: | | |
|--|--|--|
| Watertight-nema type 4 | | |
| Overall Length: | | |
| 1.310 inches | | |
| Overall Diameter: | | |
| 0.660 inches | | |
| Lamp Base Type Accommodated: | | |
| Midget flanged | | |
| Lamp Bulb Size Designator: | | |
| T-1 3/4 | | |
| Lens Quantity: | | |
| 1 | | |
| Lens Color: | | |
| Red single light 1st position horizontal | | |
| Panel Accommodation Hole Diameter: | | |
| 0.469 inches | | |
| Lens Mounting Method: | | |
| Screw in | | |
| Mounting Method: | | |
| Panel | | |
| Panel Thickness For Which Designed: | | |
| 0.220 inches | | |
| Lamp Type Accommodated And Quantity: | | |
| | | |
| 1 incandescent | | |
| 1 incandescent Lens Type: | | |
| | | |
| Lens Type: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic body | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic body Special Test Features: | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic body Special Test Features: Navord od36190 | | |
| Lens Type: Stovepipe, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic body Special Test Features: Navord od36190 Style Designator: | | |

As differentiated by special test features

Reference Number Differentiating Characteristics:

NSN 6210-00-892-6278

Indicator Light - Page 2 of 2



| | Life: |
|--|-------|
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0