## NSN 6210-00-893-1723

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-893-1723

Overall Length:
2.846 inches
Overall Diameter:
1.141 inches
Lamp Base Type Accommodated:
Candelabra screw
Lamp Bulb Size Designator:
S-6
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Panel Accommodation Hole Diameter:
1.000 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.750 inches
Lamp Type Accommodated And Quantity:
1 incandescent
1 incandescent
1 incandescent  Lens Type:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body  Style Designator:
1 incandescent  Lens Type:  Convex, knurled single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body  Style Designator:  Round frame, round lens type

2 screw

## NSN 6210-00-893-1723

Indicator Light - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A065a0