NSN 6210-00-913-5426

Panel Light - Page 1 of 2

1 hexagon nut and 1 lock washer



View Online at https://aerobasegroup.com/nsn/6210-00-913-5426

Hazardous Locations/environmental Protection:
Dusttight
Overall Length:
1.582 inches
Overall Diameter:
0.625 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Panel Accommodation Hole Diameter:
Between 0.468 inches and 0.472 inches
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.188 inches
Lamp Type Accommodated And Quantity:
Lamp Type Accommodated And Quantity: 1 incandescent
1 incandescent
1 incandescent Lens Type:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Dark gray opaque hood in accordance w/fed standard 595, color no. 36231 Material:
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Dark gray opaque hood in accordance w/fed standard 595, color no. 36231 Material: Plastic illumination directing device
1 incandescent Lens Type: Flat, edge w/boot single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Dark gray opaque hood in accordance w/fed standard 595, color no. 36231 Material:

NSN 6210-00-913-5426

Panel Light - Page 2 of 2



Terminal Type And Quantity:
2 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A065a0

Mil-std (military Standard):

Mil-I-3661 spec.