NSN 6210-00-922-0819

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-922-0819

| Hazardous Locations/environmental Protection: |
|--|
| Watertight |
| Overall Length: |
| 3.015 inches |
| Overall Diameter: |
| 1.375 inches |
| Lamp Base Type Accommodated: |
| Double contact bayonet candelabra |
| Lamp Bulb Size Designator: |
| S-6 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Green single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| 1.000 inches |
| Lens Mounting Method: |
| Screw on |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.344 inches |
| Lamp Type Accommodated And Quantity: |
| 1 incandescent |
| Lens Type: |
| Convex, knurled single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Transmitted Light Color: |
| Green single light 1st position horizontal full display division a |
| Lens Back Surface Condition: |
| Frosted single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Material: |
| Copper alloy body |
| Surface Treatment: |
| Chromium body |
| Style Designator: |
| Round frame, round lens type |
| Furnished Items And Quantity: |

1 hexagon nut and 1 lock washer

NSN 6210-00-922-0819

Indicator Light - Page 2 of 2



| Terminal Type And Quantity | / : |
|----------------------------|------------|
|----------------------------|------------|

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0