NSN 6210-00-926-7685

Hazardous Locations/environmental Protection:

Dripproof and radio frequency interference

Overall Length: 2.374 inches

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-926-7685

Overall Height:
0.750 inches
Overall Width:
1.000 inches
Filter Color:
Green single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Filter Quantity:
1
Multilamp Circuit Type:
Two lamp common
Lamp Industry Number:
387
Lens Mounting Method:
Lens Mounting Method: Flange
_
Flange
Flange Mounting Method:
Flange Mounting Method: Panel
Flange Mounting Method: Panel Panel Thickness For Which Designed:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal Panel Accommodation Hole Height:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal Panel Accommodation Hole Height: 0.670 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal Panel Accommodation Hole Height: 0.670 inches Lens Light Transmission Characteristic:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal Panel Accommodation Hole Height: 0.670 inches Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.031 inches and 0.250 inches Panel Accommodation Hole Width: 0.920 inches Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Display screen single light 1st position horizontal Panel Accommodation Hole Height: 0.670 inches Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Legend Color:

NSN 6210-00-926-7685

Indicator Light - Page 2 of 2



l anc	Legend	
LC113	Legenu	•

Speed; gate single light 1st position horizontal full display division a

Transmitted Light Color:

Green single light 1st position horizontal full display division a

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Special Features:

Dripproff seal

Material:

Stainless steel body

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

3 solder lug w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0