NSN 6210-00-926-7718

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-926-7718

Hazardous Locations/environmental Protection:							
Radio frequency interference							
Overall Length:							
1.875 inches							
Overall Diameter:							
0.553 inches							
Lens Quantity:							
1							
Lens Color:							
White single light 1st position horizontal							
Panel Accommodation Hole Diameter:							
0.375 inches							
Lens Mounting Method:							
Screw on							
Mounting Method:							
Panel							
Panel Thickness For Which Designed:							
0.312 inches							
Lamp Type Accommodated And Quantity:							
1 incandescent lamp cartridge							
Lens Type:							
Dome, knurled, internal thread single light 1st position horizontal							
Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic:							
Lens Light Transmission Characteristic:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Nickel body							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Nickel body Style Designator:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Nickel body Style Designator: Round frame, round lens type							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Nickel body Style Designator: Round frame, round lens type Furnished Items And Quantity:							
Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Aluminum body Surface Treatment: Nickel body Style Designator: Round frame, round lens type Furnished Items And Quantity: 1 hexagon nut and 1 knurled flange ring and 1 lock washer							

N/a

NSN 6210-00-926-7718

Indicator Light - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A065a0