NSN 6210-00-935-1310

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-935-1310

Overall Length:
1.573 inches
Overall Diameter:
Between 0.574 inches and 0.614 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-2
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.469 inches
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.438 inches
Lamp Type Accommodated And Quantity:
1 neon
1 neon Lens Type:
Lens Type:
Lens Type: Cylindrical, external thread single light 1st position horizontal
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Resistor designed for 105 to 125v circuit voltage range Material: Aluminum body
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Resistor designed for 105 to 125v circuit voltage range Material: Aluminum body Surface Treatment:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Resistor designed for 105 to 125v circuit voltage range Material: Aluminum body Surface Treatment: Anodize body
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Resistor designed for 105 to 125v circuit voltage range Material: Aluminum body Surface Treatment: Anodize body Style Designator:
Lens Type: Cylindrical, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Resistor designed for 105 to 125v circuit voltage range Material: Aluminum body Surface Treatment: Anodize body

1 hexagon nut and 1 lock washer

NSN 6210-00-935-1310

Indicator Light - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0