NSN 6210-00-955-2169

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-00-955-2169

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
Between 1.016 inches and 1.036 inches
Overall Diameter:
0.438 inches
Filter Color:
Red single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.375 inches
Filter Quantity:
1
Lana Marratina Mathada
Lens Mounting Method:
Screw in
Screw in
Screw in Mounting Method:
Screw in Mounting Method: Panel
Screw in Mounting Method: Panel Panel Thickness For Which Designed:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.375 inches Features Provided: Removable light filter Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal

Nickel body

NSN 6210-00-955-2169

Indicator Light - Page 2 of 2



Style Designator:
Trap type
Terminal Type And Quantity:
1 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A065a0