NSN 6210-01-022-7169

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-022-7169

Hazardous Locations/environmental Protection:
Radio frequency interference and watertight
Overall Length:
1.560 inches
Overall Diameter:
0.660 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-2
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.500 inches
Lamp Industry Number:
C9a
Lens Mounting Method:
Screw in
Mounting Mathad
Mounting Method:
Panel
-
Panel
Panel Panel Thickness For Which Designed:
Panel Panel Thickness For Which Designed: 0.312 inches
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity:
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type:
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 neon Lens Type: Dome, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Nickel body

1 gasket

NSN 6210-01-022-7169

Indicator Light - Page 2 of 2



Terminal	Type	And	Quantity:
----------	------	-----	-----------

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0