NSN 6210-01-025-4903

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-025-4903

Hazardous Locations/environmental Protection:
Radio frequency interference
Overall Length:
1.500 inches
Overall Diameter:
0.620 inches
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Green single light 1st position horizontal
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.280 inches
Features Provided:
Press to test
Lamp Type Accommodated And Quantity:
1 incandescent
Lens Type:
Lens Type: Flat, knurled, external thread single light 1st position horizontal
Flat, knurled, external thread single light 1st position horizontal
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material: Aluminum body
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material: Aluminum body Surface Treatment:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material: Aluminum body Surface Treatment: Cadmium body
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material: Aluminum body Surface Treatment: Cadmium body Style Designator:
Flat, knurled, external thread single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Press to test stamped on holder Material: Aluminum body Surface Treatment: Cadmium body Style Designator: Round frame, round lens type

3 solder lug

NSN 6210-01-025-4903

Indicator Light - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0