## NSN 6210-01-025-4903

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-025-4903

| Hazardous Locations/environmental Protection:   |
|---|
| Radio frequency interference  |
| Overall Length:   |
| 1.500 inches  |
| Overall Diameter:   |
| 0.620 inches  |
| Lamp Bulb Size Designator:  |
| T-1 3/4   |
| Lens Quantity:  |
| 1   |
| Lens Color:   |
| Green single light 1st position horizontal  |
| Lens Mounting Method:   |
| Screw on  |
| Mounting Method:  |
| Panel   |
| Panel Thickness For Which Designed:   |
| 0.280 inches  |
| Features Provided:  |
| Press to test   |
| Lamp Type Accommodated And Quantity:  |
| 1 incandescent  |
|   |
| Lens Type:  |
| Lens Type: Flat, knurled, external thread single light 1st position horizontal  |
|   |
| Flat, knurled, external thread single light 1st position horizontal   |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal   |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:   |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:   |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:   |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:  Aluminum body  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:  Aluminum body  Surface Treatment:  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:  Aluminum body  Surface Treatment:  Cadmium body  |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:  Aluminum body  Surface Treatment:  Cadmium body  Style Designator:                               |
| Flat, knurled, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Special Features:  Press to test stamped on holder  Material:  Aluminum body  Surface Treatment:  Cadmium body  Style Designator:  Round frame, round lens type |

3 solder lug

## NSN 6210-01-025-4903

Indicator Light - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A065a0