

View Online at <https://aerobasegroup.com/nsn/6210-01-037-7231>

Hazardous Locations/environmental Protection:

Fungus resistant and moisture resistant and shock resistant and vibration resistant

Overall Length:

2.720 inches

Overall Height:

0.904 inches

Overall Width:

1.154 inches

Filter Color:

Yellow single light 1st position horizontal horizontal split display division b

Lamp Base Type Accommodated:

Midget flanged

Lamp Bulb Size Designator:

T-1 3/4

Lens Quantity:

1

Lens Color:

White single light 1st position horizontal

Filter Quantity:

4

Multilamp Circuit Type:

Four lamp common

Lamp Industry Number:

387

Lens Mounting Method:

Flange

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.060 inches and 0.188 inches

Panel Accommodation Hole Width:

Between 1.000 inches and 1.010 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, rectangular single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.755 inches and 0.765 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

Black single light 1st position horizontal horizontal split display division b

Lens Legend:

Overtemp; warning single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Yellow single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Special Features:

Stainless steel bezel; spacer dim. 0.870 in. Lg; mtg sleeve size 1.260 in. Lg

Material:

Aluminum alloy 5052 body

Surface Treatment:

Anodize body

Style Designator:

Rectangular frame type

Furnished Items And Quantity:

1 clear plastic diffuser and 1 lock washer and 1 mounting sleeve and 1 spacer and 1 screw

Terminal Type And Quantity:

5 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0