## NSN 6210-01-058-8923

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-058-8923

Overall Length:
2.249 inches
Overall Diameter:
Between 0.933 inches and 0.973 inches
Lamp Base Type Accommodated:
Miniature bayonet
Lamp Bulb Size Designator:
T-3 1/4
Lens Quantity:
1
Lens Color:
Red single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.688 inches
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.406 inches
Lamp Type Accommodated And Quantity:
Lamp Type Accommodated And Quantity.
1 incandescent
1 incandescent
1 incandescent  Lens Type:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Chromium body
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Chromium body  Style Designator:
1 incandescent  Lens Type:  Stovepipe, external thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Red single light 1st position horizontal full display division a  Lens Back Surface Condition:  Fluted single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Chromium body  Style Designator:  Round frame, round lens type

2 screw

## NSN 6210-01-058-8923

Indicator Light - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A065a0