Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-061-5527

| Hazardous Locations/environmental Protection:   |
|---|
| Watertight  |
| Overall Diameter:   |
| 0.680 inches  |
| Lamp Base Type Accommodated:  |
| Midget flanged  |
| Lamp Bulb Size Designator:  |
| T-1 3/4   |
| Lens Quantity:  |
| 1   |
| Lens Color:   |
| Green single light 1st position horizontal  |
| Panel Accommodation Hole Diameter:  |
| Between 0.485 inches and 0.515 inches   |
| Lens Mounting Method:   |
| Screw in  |
| Mounting Method:  |
| Panel   |
| Panel Thickness For Which Designed:   |
| 0.160 inches  |
| Features Provided:  |
| Dimming device  |
| Lamp Type Accommodated And Quantity:  |
|   |
| 1 incandescent  |
| 1 incandescent<br>Lens Type:  |
|   |
| Lens Type:  |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal  |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a<br>Lens Back Surface Condition:   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a<br>Lens Back Surface Condition:<br>Smooth single light 1st position horizontal  |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a<br>Lens Back Surface Condition:<br>Smooth single light 1st position horizontal<br>Lens Face Surface Condition:  |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a<br>Lens Back Surface Condition:<br>Smooth single light 1st position horizontal<br>Lens Face Surface Condition:<br>Smooth single light 1st position horizontal   |
| Lens Type:<br>Flat, knurled, threaded shank single light 1st position horizontal<br>Lens Light Transmission Characteristic:<br>Transparent single light 1st position horizontal<br>Transmitted Light Color:<br>Green single light 1st position horizontal full display division a<br>Lens Back Surface Condition:<br>Smooth single light 1st position horizontal<br>Lens Face Surface Condition:<br>Smooth single light 1st position horizontal<br>Material:  |
| <ul> <li>Lens Type:</li> <li>Flat, knurled, threaded shank single light 1st position horizontal</li> <li>Lens Light Transmission Characteristic:</li> <li>Transparent single light 1st position horizontal</li> <li>Transmitted Light Color:</li> <li>Green single light 1st position horizontal full display division a</li> <li>Lens Back Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Lens Face Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Material:</li> <li>Aluminum body</li> </ul>   |
| <ul> <li>Lens Type:</li> <li>Flat, knurled, threaded shank single light 1st position horizontal</li> <li>Lens Light Transmission Characteristic:</li> <li>Transparent single light 1st position horizontal</li> <li>Transmitted Light Color:</li> <li>Green single light 1st position horizontal full display division a</li> <li>Lens Back Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Lens Face Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Material:</li> <li>Aluminum body</li> <li>Surface Treatment:</li> </ul>                       |
| <ul> <li>Lens Type:</li> <li>Flat, knurled, threaded shank single light 1st position horizontal</li> <li>Lens Light Transmission Characteristic:</li> <li>Transparent single light 1st position horizontal</li> <li>Transmitted Light Color:</li> <li>Green single light 1st position horizontal full display division a</li> <li>Lens Back Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Lens Face Surface Condition:</li> <li>Smooth single light 1st position horizontal</li> <li>Material:</li> <li>Aluminum body</li> <li>Surface Treatment:</li> <li>Anodize body</li> </ul> |

1 hexagon nut and 1 lock washer

## NSN 6210-01-061-5527

Indicator Light - Page 2 of 2



2 solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A065a0

