

View Online at <https://aerobasegroup.com/nsn/6210-01-071-8826>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

1.260 inches

**Overall Diameter:**

0.509 inches

**Lens Quantity:**

1

**Lens Color:**

Amber single light 1st position horizontal

**Panel Accommodation Hole Diameter:**

0.375 inches

**End Application:**

Ticonderoga class c (47); arleigh burke class ddg; forrestal class cv; submarine auxillary and miscellaneous systems; trident hull structure; nimitz class cvn; spruance class dd(963); oliver perry class ffg; consolidated space operations center; wasp class lhd; aircraft, prowler ea-6b; tarawa class lha

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

0.312 inches

**Lamp Type Accommodated And Quantity:**

1 light emitting diode

**Lens Type:**

Cylindrical, knurled single light 1st position horizontal

**Lens Light Transmission Characteristic:**

Transparent single light 1st position horizontal

**Transmitted Light Color:**

Amber single light 1st position horizontal full display division a

**Lens Back Surface Condition:**

Fresnel single light 1st position horizontal

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Material:**

Aluminum body

**Surface Treatment:**

Anodize body

**Style Designator:**

Round frame, round lens type

**Furnished Items And Quantity:**

1 hexagon nut and 1 lock washer and 1 knurled flange ring

**Terminal Type And Quantity:**

2 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A065a0