

View Online at <https://aerobasegroup.com/nsn/6210-01-071-8826>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.260 inches

Overall Diameter:

0.509 inches

Lens Quantity:

1

Lens Color:

Amber single light 1st position horizontal

Panel Accommodation Hole Diameter:

0.375 inches

End Application:

Ticonderoga class c (47); arleigh burke class ddg; forrestal class cv; submarine auxillary and miscellaneous systems; trident hull structure; nimitz class cvn; spruance class dd(963) ; oliver perry class ffg; consolidated space operations center; wasp class lhd; aircraft, prowler ea-6b; tarawa class lha

Mounting Method:

Panel

Panel Thickness For Which Designed:

0.312 inches

Lamp Type Accommodated And Quantity:

1 light emitting diode

Lens Type:

Cylindrical, knurled single light 1st position horizontal

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Light Color:

Amber single light 1st position horizontal full display division a

Lens Back Surface Condition:

Fresnel single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Aluminum body

Surface Treatment:

Anodize body

Style Designator:

Round frame, round lens type

Furnished Items And Quantity:

1 hexagon nut and 1 lock washer and 1 knurled flange ring

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0