NSN 6210-01-089-5483

Lighting Fixture - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-089-5483

| Hazardous Locations/environmental Protection: |
|---------------------------------------------------------------------------------------------------------------|
| Watertight |
| Overall Length: |
| Between 28.671 inches and 28.703 inches |
| Overall Height: |
| 4.375 inches |
| Overall Width: |
| Between 7.281 inches and 7.312 inches |
| Lamp Base Type Accommodated: |
| Medium bipin |
| Wiring Provision Method: |
| Cable |
| Illumination Directing Device Type: |
| Louver and window |
| Wiring Provision Length: |
| 120.0 inches all provisions |
| Voltage Rating In Volts: |
| 115.0 ac |
| Mounting Method: |
| Bolt |
| Features Provided: |
| Switch |
| Lamp Type Accommodated And Quantity: |
| 2 fluorescent |
| Material: |
| Plastic acrylic illumination directing device |
| Material Specification: |
| Mil-p-24191, ty wtls-4, grade g military specification single material response illumination directing device |
| Shape: |
| Rectangular |
| Furnished Items And Quantity: |
| 2 lamp and 4 lg securing screw assembly |
| Terminal Type And Quantity: |
| 3 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A06300 |

NSN 6210-01-089-5483

Lighting Fixture - Page 2 of 2



Mil-std (military Standard):

Mil-p-24191 spec.