NSN 6210-01-089-9865

Hazardous Locations/environmental Protection:

Indicator Light - Page 1 of 2

Shock resistant



View Online at https://aerobasegroup.com/nsn/6210-01-089-9865

Overall Length:
3.120 inches
Overall Height:
0.870 inches
Overall Width:
0.870 inches
Filter Color:
Green single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Filter Quantity:
1
Multilamp Circuit Type:
Four lamp common
Lana Marintina Mathadi
Lens Mounting Method:
Push in
Push in
Push in Mounting Method:
Push in Mounting Method: Panel
Push in Mounting Method: Panel Panel Thickness For Which Designed:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Panel Accommodation Hole Height:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Panel Accommodation Hole Height: Between 0.742 inches and 0.750 inches
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Panel Accommodation Hole Height: Between 0.742 inches and 0.750 inches Lens Light Transmission Characteristic:
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Panel Accommodation Hole Height: Between 0.742 inches and 0.750 inches Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Push in Mounting Method: Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.125 inches Panel Accommodation Hole Width: Between 0.742 inches and 0.750 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Panel Accommodation Hole Height: Between 0.742 inches and 0.750 inches Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:

NSN 6210-01-089-9865

Indicator Light - Page 2 of 2



Lens Face Surface Condition:
Smooth single light 1st position horizontal
Special Features:
Additional furnished item and quantity: receptacle 1
Material:
Aluminum body
Surface Treatment:
Anodize body
Style Designator:
Rectangular frame type
Furnished Items And Quantity:
1 mounting sleeve
Terminal Type And Quantity:
5 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A065a0