

View Online at <https://aerobasegroup.com/nsn/6210-01-101-6157>

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant

**Overall Length:**

1.375 inches

**Overall Diameter:**

0.360 inches

**Lens Quantity:**

1

**Lens Color:**

Red single light 1st position horizontal

**End Application:**

Spruance class dd (963); ticonderoga class c (47); virginia class cgn (41); fire control system, missile mk 74(fcs); nimitz class cvn; kidd class ddg; forrestal class cv; sonar signal processing sys, an/sqq-28(v); radar set, lightweight 3d (an/tps-59) ; arleigh burke class ddg

**Mounting Method:**

Integral threaded nut

**Panel Thickness For Which Designed:**

0.125 inches

**Panel Accommodation Hole Width:**

0.250 inches

**Lamp Type Accommodated And Quantity:**

1 neon

**Lens Type:**

Cylindrical single light 1st position horizontal

**Lens Light Transmission Characteristic:**

Transparent single light 1st position horizontal

**Transmitted Light Color:**

Red single light 1st position horizontal full display division a

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Material:**

Aluminum body

**Surface Treatment:**

Anodize body

**Style Designator:**

Round frame, round lens type

**Furnished Items And Quantity:**

1 lock washer

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A065a0