

View Online at <https://aerobasegroup.com/nsn/6210-01-101-6157>

Hazardous Locations/environmental Protection:

Humidity resistant and vibration resistant

Overall Length:

1.375 inches

Overall Diameter:

0.360 inches

Lens Quantity:

1

Lens Color:

Red single light 1st position horizontal

End Application:

Spruance class dd (963); ticonderoga class c (47); virginia class cgn (41); fire control system, missile mk 74(fcs); nimitz class cvn; kidd class ddg; forrestal class cv; sonar signal processing sys, an/sqq-28(v); radar set, lightweight 3d (an/tps-59) ; arleigh burke class ddg

Mounting Method:

Integral threaded nut

Panel Thickness For Which Designed:

0.125 inches

Panel Accommodation Hole Width:

0.250 inches

Lamp Type Accommodated And Quantity:

1 neon

Lens Type:

Cylindrical single light 1st position horizontal

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Light Color:

Red single light 1st position horizontal full display division a

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Aluminum body

Surface Treatment:

Anodize body

Style Designator:

Round frame, round lens type

Furnished Items And Quantity:

1 lock washer

Terminal Type And Quantity:

2 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0