## NSN 6210-01-111-4642

Light Lens - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/6210-01-111-4642

| view Offilite at https://aerobasegroup.com/hist//o210-01-1111-4042                      |
|---|
| Thread Class:   |
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Hazardous Locations/environmental Protection:   |
| Moisture resistant and salt water resistant and shock resistant and vibration resistant |
| Overall Length:   |
| Between 0.640 inches and 0.660 inches   |
| Effective Length:   |
| 0.400 inches  |
| Mounting Device Quantity:   |
| 1   |
| Effective Diameter:   |
| 0.500 inches  |
| Mounting Method:  |
| External thread   |
| Thread Series:  |
| Unef  |
| Features Provided:  |
| Rotatable alignment capability  |
| Light Transmission Design:  |
| Translucent lens  |
| Inscription:  |
| 2 within a circle insert  |
| Thread Quantity:  |
| 32 per inch   |
| Holder Surface Treatment:   |
| Anodize   |
| Thread Diameter:  |
| 0.216 inches  |
| Color:  |
| White inscription   |
| Material:   |
| Plastic polycarbonate lens  |
| Material Specification:   |
| L-p-393 federal specification single material response lens                             |
| Surface Condition:  |
| Smooth back   |
| Style Designator:   |
| Flat  |
| Shelf Life:   |

## NSN 6210-01-111-4642

Light Lens - Page 2 of 2



|    | • • |             |    |     |      |
|----|-----|-------------|----|-----|------|
| In | 18  | <i>(</i> )+ | МА | 261 | ıre: |
|    |     |             |    |     |      |

--

Demilitarization:

No

Fiig:

A528d0